




SL34BF

SURFACE MOUNT SCHOTTKY BARRIER RECTIFIER

Reverse Voltage - 40 Volts Forward Current - 3.0 Ampere

SMBF



Dimensions in inches and (millimeters)

FEATURES

- ◆ Metal silicon junction, majority carrier conduction
- ◆ For surface mounted applications
- ◆ Low power loss, high efficiency
- ◆ High forward surge current capability
- ◆ For use in low voltage, high frequency inverters, free wheeling, and polarity protection applications

MECHANICAL DATA

Case: JEDEC SMBF molded plastic body

Terminals: leads solderable per MIL-STD-750, Method 2026

Mounting Position: Any

Weight: 57mg/0.002oz

MAXIMUM RATINGS AND ELECTRICAL CHARACTERISTICS

Ratings at 25°C ambient temperature unless otherwise specified.

Single phase half-wave 60Hz, resistive or inductive load, for capacitive load current derate by 20%.

TWGMC Catalog Number	SYMBOLS	SL34BF	UNITS
Maximum repetitive peak reverse voltage	V_{RRM}	40	VOLTS
Maximum RMS voltage	V_{RMS}	28	VOLTS
Maximum DC blocking voltage	V_{DC}	40	VOLTS
Maximum average forward rectified current	$I_{(AV)}$	3.0	Amp
Peak forward surge current 8.3ms single half sine-wave superimposed on rated load (JEDEC Method)	I_{FSM}	80.0	Amps
Maximum instantaneous forward voltage at 3.0A	V_F	0.45	Volts
Maximum DC reverse current $T_A=25^\circ\text{C}$ at rated DC blocking voltage $T_A=100^\circ\text{C}$	I_R	0.3 5.0	mA
Typical junction capacitance (NOTE 1)	C_J	450	pF
Typical thermal resistance (NOTE 2)	$R_{\theta JA}$	50.0	°C/W
Operating junction temperature range	T_{JL}	-50 to +125	°C
Storage temperature range	T_{STG}	-50 to +150	°C

Note: 1. Measured at 1MHz and applied reverse voltage of 4.0V D.C.

2. P.C.B. mounted with 0.5x0.5" (12.7x12.7mm) copper pad areas

RATINGS AND CHARACTERISTIC CURVES SL34BF

Fig.1 Forward Current Derating Curve




Fig.2 Typical Reverse Characteristics




Fig.3 Typical Forward Characteristic




Fig.4 Typical Junction Capacitance




Fig.5 Maximum Non-Repetitive Peak Forward Surge Current




Fig.6- Typical Transient Thermal Impedance

