




ES2ABF THRU ES2JBF

SURFACE MOUNT SUPERFAST RECOVERY RECTIFIER

Reverse Voltage - 50 to 600 Volts Forward Current - 2.0 Amperes

SMBF



FEATURES

- ◆ For surface mounted applications
- ◆ Low profile package
- ◆ Glass Passivated Chip Junction
- ◆ Superfast reverse recovery time
- ◆ Lead free in comply with EU RoHS 2011/65/EU directives

MECHANICAL DATA

Case: JEDEC SMBF molded plastic body
Terminals: leads solderable per MIL-STD-750, Method 2026
Mounting Position: Any
Weight: 57mg/0.002oz

MAXIMUM RATINGS AND ELECTRICAL CHARACTERISTICS


Ratings at 25°C ambient temperature unless otherwise specified.
Single phase half-wave 60Hz, resistive or inductive load, for capacitive load current derate by 20%.

TWGMC Catalog Number	SYMBOLS	ES2ABF	ES2BBF	ES2DBF	ES2GBF	ES2JBF	UNITS
Marking code		E2AB	E2BB	E2DB	E2GB	E2JB	
Maximum repetitive peak reverse voltage	V _{RRM}	50	100	200	400	600	VOLTS
Maximum RMS voltage	V _{RMS}	35	70	140	280	420	VOLTS
Maximum DC blocking voltage	V _{DC}	50	100	200	400	600	VOLTS
Maximum average forward rectified current at T _L =100°C	I _(AV)	2.0					Amps
Peak forward surge current 8.3ms single half sine-wave superimposed on rated load (JEDEC Method)	I _{FSM}	50					Amps
Maximum instantaneous forward voltage at 2.0A	V _F	1.0			1.25	1.65	Volts
Maximum DC reverse current T _A =25°C at rated DC blocking voltage T _A =125°C	I _R	5.0 100.0					μA
Maximum reverse recovery time (NOTE 1)	t _{rr}	35					ns
Typical junction capacitance (NOTE 2)	C _J	45.0					pF
Typical thermal resistance (NOTE 3)	R _{θJA}	65.0					°C/W
Operating junction and storage temperature range	T _J ,T _{STG}	-55 to +150					°C

Note: 1. Reverse recovery condition $I_F=0.5\text{A}$, $I_R=1.0\text{A}$, $I_{rr}=0.25\text{A}$
2. Measured at 1MHz and applied reverse voltage of 4.0V D.C.
3. P.C.B. mounted with 0.5x0.5" (12.7x12.7mm) copper pad areas

RATINGS AND CHARACTERISTIC CURVES ES2ABF THRU ES2JBF

Fig.1 Reverse Recovery Time Characteristic And Test Circuit Diagram



Note: 1. Rise Time = 7ns, max.
Input Impedance = 1megohm, 22pF.
2. Rise Time = 10ns, max.
Source Impedance = 50 ohms.




Fig.2 Maximum Average Forward Current Rating




Fig.3 Typical Reverse Characteristics




Fig.4 Typical Forward Characteristics




Fig.5 Typical Junction Capacitance




Fig.6 Maximum Non-Repetitive Peak Forward Surge Current

